

PRECAUTIONS: Breathing protection is NOT required but always recommended. If the product gets on bare skin use mild soap and warm water to remove. If the product gets in your eyes, rinse out fully with warm water.

CAN BE USED ON: STEM WALL, STUCCO, BRICK, BLOCK, CONCRETE, PAINTED SUBSTRATES. PROPER VENTILATION AREA RECOMMENDED FOR CRIB LEGS, GRILLS, PATIO FURNITURE, INTERIOR SURFACES

INSTRUCTIONS

APPLICATION

PREP

1. Clean and prep the area, move away rocks, dirt and debris away from the foundation. Spray off with hose and/or wash with water and soap.
2. After cleaning the application area, sweep away dirt debris off hard surfaces such as pavers, concrete or tile.
3. Once the tape is protecting the hard surface, it's recommended but optional to place additional protection using newspaper, masking paper, or a tarp on top of the tape and against the stem wall. This will prevent drips and spills.

APPLICATION

4. Use a 2"-3" paint brush to apply the product onto the perimeter of the stem wall. When applying the product, start with 1 coat around the home (full circle, don't miss any spots around home) **Pour the product into a bucket to easily transport the coating while you apply it onto the stem wall around the home (optional).
5. After you've applied the first coat onto the full perimeter of the home, the second coat will be ready for application. Use a TCP global wet film thickness gauge to measure the application while wet. Be sure the 25 mil tooth is wet for correct product specification measurement. (wait 30-60 minutes to apply the second coat or until dry).
6. Once the application is completed, clean pre application taping and coverage by rolling it up and disposing of it into a trash bag.
7. Walk around the home to check for any missing areas. Apply product to these areas as necessary.
8. Most surfaces require 2 coats, some porous surfaces may require additional coats.

PRODUCT SPECIFICATION:

RANGE OF ROOT MEAN SQUARE. RMS: ROOT MEAN SQUARE 'ROUGHNESS MEASUREMENT'. NEEDED FOR EFFECTIVE INSECTS CONTROL. ROUGHNESS AVERAGE '9 μ m' RA. RANGE OF COATING THICKNESS NEEDS TO BE: 30 MIL THICKNESS WHEN WET. 16 MIL THICKNESS WHEN DRY. 1 GALLON = 100 LINEAR FEET.

For any further questions, feel free to call us at 480-202-5500 or email us at info@95applications.com

Proprietary trade secret protected. Creates a tile like glaze smooth coating on vertical surfaces strategically applied around structures and items. Used as a physical barrier on vertical surfaces in order to discourage access. Only to be used for written consent of 95 Applications™ LLC.

product is a branded product and Proprietary Intellectual Property owned by 95 applications™.

APPLICATION INSTRUCTIONS:

Not for resale and commercial use ONLY. Please refer to 95 Applications™ Certified Technician and/or the 95 Applications™ Operation Manual for additional instructions.

CLEAN UP:

Mild soap and water if wet. You can use paint thinner if dry.

COVERAGE RATES:

One gallon will cover approximately 100 to 300 linear feet at 4in height.

PRECAUTIONARY STATEMENTS:

GENERAL: KEEP OUT OF THE REACH OF CHILDREN. **PREVENTION:** Do not handle it until all safety precautions have been read and understood. Obtain special instructions before use. Do not eat, drink or smoke when using this product. NOT required but wearing eye protection, protective clothing, protective gloves is recommended. **RESPONSE:** If on skin (or hair): Us mild soap and warm water to remove. **STORAGE:** Store in a well-ventilated place. Keep cool. Store locked up. **DISPOSAL:** Allow the container to dry and throw away. Do not remove any labeling.

CONTACT YOUR LOCAL POISON CONTROL CENTER OR CALL 1-800-457-4280 (NORTH AMERICA). INFOTRAC 01-352-323-3500 9INTERNATIONAL).

PATENT

MANUFACTURED FOR: 95 Applications™, Gilbert, AZ 480-202-5500

U.S. Pat. App. Ser. No. 16/709,371 U.S. Pat. App. Ser. No. 17/010,803 U.S. Prov. Pat. App. Ser. No. 63/119,589